

# Miscellaneous Technical Information







A brand of  
BASF - We create chemistry

## 70U-15 Degreaser





### 1. Properties / Information

- 70U-15 Degreaser is a silicone, wax, grease, tar and road-oil dissolving solvent. 70U-15 will remove contamination from existing paint films, slightly penetrate existing paint for good adhesion of subsequent coats, and clean sanded OEM finishes for repairing.

### 2. Application

	Mixing ratio	Ready for use
	Pot life at 68°F / 20°C	N/A
	Spray viscosity Ford 4 at 68°F / 20°C	N/A
	Spray gun HVLP	N/A
	Spray pressure HVLP at the cap	N/A
	Application	Wash with liberal amounts of 70U-15 using clean cloths. While still wet, wipe dry using clean dry cloths to remove residual contamination. Change cloths frequently. Do not allow to dry on surface or remain in contact with lacquer finishes for extended periods of time.
	Film thickness	N/A
	Coverage	N/A

### 3. Flash off / Drying / Sanding

	Flash-off at 68°F / 20°C	N/A
	Drying at 68°F / 20°C at 140°F / 60°C	N/A N/A
	Infrared short wave medium wave	N/A N/A
	Wet sand by Hand	N/A
	Dry sand by Hand	N/A
	Dry sand by Machine	N/A

### 4. VOC / Comments

VOC as supplied	758 gms/ltr (6.3 lbs/gal)
Comments	Do not use 70U-15 on plastic parts.

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous & should be used according to label directions & technical data information. Appropriate respiratory protection should be worn at all times while products are in use — read product label and Safety Data Sheet (SDS) for specific details. Statements & methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only & are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.