

Miscellaneous Technical Information



A brand of
BASF - We create chemistry

80U-20 Matte Additive

1. Properties / Information

- 80U-20 Matte Additive is a flattening agent that may be added to baslac Clearcoats for gloss reduction. 80U-20 mixes easily and allows flattening to the extent desired.

2. Application



Mixing

Stir product thoroughly for 5 - 10 minutes before using.

Add up to 100% of 80U-20 to Ready For Use clearcoat. Additional reduction is optional.

Ensure proper flash-off periods are observed when spraying flattened products to prevent additional gloss.

Polishing finishes containing 80U-20 will cause gloss levels to increase.

3. Comments

Comments

DO NOT use 80U-20 in any Basecoat color.

Can be mixed with any Low VOC baslac product and still be VOC compliant.

Materials described are for application by professional trained personnel only using proper equipment. Products may be hazardous & should be used according to label directions & technical data information. Appropriate respiratory protection should be worn at all times while products are in use — read product label and Safety Data Sheet (SDS) for specific details. Statements & methods described are based upon the latest standard of technology known to the manufacturer. Application procedures cited are suggestions only & are not to be interpreted as warranty for events resulting from their use. Dilution ratios are intended to provide maximum performance within the typical Volatile Organic Compound (VOC) restriction for product use. Specific VOC limits need to be referenced to verify local compliance. Altering the solvent or dilution ratio may impact VOC compliance. User is solely responsible to ensure product use and application is in accordance with all applicable regulatory, legislative, and municipal requirements.