

Technical Information

65-10



Blending Reducer

Blend-in reducer for baslac clears 40-

- Blend-in reducer to melt in overspray / overlap areas or to melt in clear coat

Application



Ready for use



HVLP spray gun

Nozzle size	1.3 mm
Application pressure	2 bar
Nozzle pressure	0.7 bar



Number of spray coats

2 -3 (clear coat fade-out areas)

Drying



Drying at 20°C

As recommended for the baslac clear used

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

2004/42/IIB(cIII)(780)760: The EU limit value for this product (product category: IIB.cIII) in ready to use form is max 780 g/l of VOC. The VOC content of this product is 760 g/l.

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.