Technical Information Chart 2



Pre-treatment of substrates and old paintwork

Bare steel and aluminium repair

Cleaning / sanding

70-10 Silicone Remover





70-10 **Silicone** Remover







70-10 **Silicone** Remover





wipe dry

New panels (factory primed)

Cleaning / sanding

70-10 Silicone Remover













Plastics and GRP/SMC

Plastics

70-20 Cleaner **Plastic**





sanding pad

70-20 Cleaner







Heating

PU foam and polyamide (PA) must be heated for 1 hour at 60°C to remove mould release agents and water

70-20

Cleaner

Plastic



moistened cloth

GRP / SMC

70-20 Cleaner **Plastic**





wipe dry



P 180-240



wipe dry

Safety instructions:

The products are suitable for professional use only. It cannot be ruled out that this product contains particles < 0.1 µm.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

BASF Coatings GmbH, Automotive Refinish Coatings Solutions, Europe, Glasuritstraße 1, 48165 Münster, Germany, 04/2021

